


Issue of 06.04.2016
replaces all earlier issues

EUKALIN

SPEZIAL-KLEBSTOFF FABRIK GMBH

Ernst-Abbe-Str. 10
52249 Eschweiler
Telefon +49 (0) 24 03-64 50-0
Telefax +49 (0) 24 03-64 50-26
E-Mail eukalin@eukalin.de
www.eukalin.de



Technical Data Sheet

Hotmelt adhesive EUKALIN 441 VB

EUKALIN 441 VB is a blend of resins, waxes and a polymer.

Application

The product is suited for gluing different materials i.e. carton sealing. More detailed information about possible applications is available on request in written form or from our technical service.

Technical data and working instructions

| | |
|-----------------------------------|---|
| Viscosity (170°C) (Brookfield) | 1250 mPa*s +- 15% |
| Density: | 0.93 +/- 0.1 g/ml |
| Colour: | white |
| Working temperature: | 160°C, do not mix with other products |
| Storage: | in closed original containers at temperatures not exceeding 30°C : up to 12 months |

This information is based on the present state of our knowledge and practical experience. Due to the large variety of products, materials and operating conditions beyond our control, the purchasers are in all cases recommended to make sufficient tests under production circumstances to determine the suitability of the product, or to take respectively contact with our technical staff. We can not give any guarantee or accept liability regarding the above mentioned specifications, neither resulting from oral consultancy.