

Issue of 08.03.2018
replaces all earlier issues

EUKALIN

SPEZIAL-KLEBSTOFF FABRIK GMBH

Ernst-Abbe-Str. 10
52249 Eschweiler
Telefon +49 (0) 24 03-64 50-0
Telefax +49 (0) 24 03-64 50-26
E-mail eukalin@eukalin.de
www.eukalin.de

Data sheet

Hot melt adhesive EUKALIN 604 VB

EUKALIN 604 VB is a blend of resins, waxes and a polymer.

Application

The product is suited for gluing different materials or for the production of coatings. More detailed information about possible applications is available on request in written form or from our technical service.

Technical data and working instructions

| | |
|---------------------------------------|--|
| COLOUR | white |
| PROCESSING TEMPERATURE | 150°C - 170°C |
| VISCOSITY (Brookfield DVII+) 160°C | 1750 mPas +-25% |
| WORKING TEMPERATURE | please see temperature from viscosity above |
| STORAGE | in closed original container at temperatures lower than 30°C up to 24 months after date of shipping. |

Previous information is based on our practice oriented experience and is made to the best of our knowledge. It does not present any guarantee concerning condition. Due to the different materials and the working conditions beyond our influence we recommend conducting sufficient self tests in any case, as well as contacting our application services. Because of the above mentioned reasons we are not liable - despite in case of intention, gross negligence or injuries to life, body or health - for the correctness of the above mentioned information as well as for otherwise given advices.