

Issue of 12.08.2020
replaces all earlier issues

EUKALIN

SPEZIAL-KLEBSTOFF FABRIK GMBH

Ernst-Abbe-Str. 10
52249 Eschweiler
Telefon +49 (0) 24 03-64 50-0
Telefax +49 (0) 24 03-64 50-26
E-mail eukalin@eukalin.de
www.eukalin.de

Data sheet

Synthetic resin adhesive EUKALIN 8910

EUKALIN 8910 is a water based synthetic resin dispersion.

Application

The product is suited for gluing different materials or for the production of coatings. More detailed information about possible applications is available on request in written form or from our technical service.

Technical data and working instructions

VISCOSITY (Brookfield DVII+) 20°C	2600 mPas +-20%
DILUTION	possible with water
STORAGE	in closed original container at 10-30°C 6 months after date of shipment. Do not store below 0°C. Use at ambient temperature.

Previous information is based on our practice oriented experience and is made to the best of our knowledge. It does not present any guarantee concerning condition. Due to the different materials and the working conditions beyond our influence we recommend conducting sufficient self tests in any case, as well as contacting our application services. Because of the above mentioned reasons we are not liable - despite in case of intention, gross negligence or injuries to life, body or health - for the correctness of the above mentioned information as well as for otherwise given advices.